



PALLET EXPANDER

TOOLS FOR THE SPECIALIST



+

SABRE SAW

OUR SUITABLE ACCESSORIES

PNEUMATIC



TECHNICAL DATA

PALLET EXPANDER

The single acting pneumatic cylinder separates the top and bottom plate of a wooden pallet and allows to cut the nails with a sabre saw.



			PNEUMATIC 					OPERATING PRESSURE		4-8 Bar			
ORDER NO.	Piston stroke	Holder spacing	Expanding power at					Air consumption	Connection	Noise level LpA	Vibration level	Weight	
			4 bar	5 bar	6 bar	7 bar	8 bar						
	mm	mm	KN	KN	KN	KN	KN	l/Hub		dB(A)	m/s²	kg	
7 2510 0010	42.00	90.00	1.26	1.63	1.99	2.36	2.72	0.17	R 1/4" female	<70.0	<2.5	2.7	
7 2511 0010	28.00	90.00	1.26	1.63	1.99	2.36	2.72	0.11	R 1/4" female	<70.0	<2.5	2.5	
7 2512 0010	42.00/62.00	90.00	1.26	1.63	1.99	2.36	2.72	0.17	R 1/4" female	<70.0	<2.5	2.7	

Subject to technical change.

Performance data at an operating pressure of 4-8 bar.

SABRE SAW

Pneumatic sabre saw with increased cutting speed and quick release tool adapter.



ORDER NO.	Power	Air consumption	Stroke	Number of strokes	Noise level LpA	Vibration level chipboard/wooden beam	Weight
	kW	m ³ /min	mm	rpm	dB(A)	m/s ²	kg
5 1237 0010	1.8	2.0	28	2,800	90	18.3/28.3	4.9

Subject to technical change.

Performance data at an operating pressure of 6 bar.

CONSTRUCTION TOOLS PROGRAM

NEEDLE SCALERS



RIVETING AND CHIPPING HAMMERS



SHEAR HAMMERS



SAND RAMMERS



MIXERS



PALETT EXPANDERS

